

TUBO POLIAMIDA



MATERIAL

- Poliamida 6

TEMPERATURA DE TRABAJO

- -40°C/ 120°C








CARACTERÍSTICAS

- Libre de halógenos
- Temperatura máxima (240H) 150°C
- Retardante a la llama








			 Int. mm x  Ext. mm	 ■	 ■
	200	3	2,8 x 5,1	1200073	
	100	4,5	5,0 x 7,1	1200068	
	100	6	6,0 x 9,2	1200069	
	50	7,5	6,7 x 10,0	1200070	1203907
PG 7	50	8,5	8,4 x 11,7	1200089	1203908
PG 9	50	10	9,9 x 13,0	1200100	1203910
PG 11	50	12	12,2 x 15,7	1200127	1203912
PG 11	50	13	12,7 x 15,8	1200135	1203913
PG 13,5	50	14	14,2 x 18,5	1200143	1203914
	50	16	15,5 x 18,9	1200160	
PG 16	50	17	16,6 x 21,2	1200178	1203917
	50	19	19,3 x 24,3	1200194	
PG 21	50	22	21,3 x 25,4	1200224	1203922
PG 21	50	23	23,2 x 28,3	1200232	1203923
	50	26	25,8 x 31,2	1200267	
PG 29	25	29	29,0 x 34,5	1200291	1203929
PG 36	25	37	36,0 x 42,4	1200372	1203937
PG 48	25	50	47,7 x 54,0	1200500	1203950