

BASES UNIPOLARES CERRADAS (BUC) DESCONECTABLES EN CARGA

IEC-UNE-EN 60947/3 IP-20



Con indicador luminoso de fusión. Fijación tornillo.

In(A)		
160	1	1020.6001
160	1	1020.6002
160	1	1020.6003
160	1	1020.6004
250	1	1020.6005
250	1	1020.6006
250	1	1020.6007
250	1	1020.6008
250	1	1020.6009
250	1	1020.6010
250	1	1020.6011
630	1	1020.6012
630	1	1020.6013
630	1	1020.6014

BASES TRIPOLARES VERT. CERRADAS (BTVC) DESCONECTABLES EN CARGA



Con indicador luminoso de fusión.

Fijación: Pletina 185 mm.

In(A)	CONEX.		
160	Tornillo M10 inox.	1	1020.6030
250	Tornillo M10 inox.	1	1020.6031
400	Tornillo M10 inox.	1	1020.6032
630	Tornillo M10 inox.	1	1020.6033

SECCIONADORES TRIPOLARES HORIZONTALES (BTHC)



Fijación: Tornillo

TIPO	In(A)		
M8	160	1	1020.6017
M10	250	1	1020.6018
M10	400	1	1020.6019
M12	630	1	1020.6020

Fijación: Pletina

TIPO	In(A)		
M8	160	1	1020.6022
M10	250	1	1020.6023
M10	400	1	1020.6024
M12	630	1	1020.6025