

ENCHUFABLES HEMBRA CILÍNDRICO DOBLE CASQUILLO



		Sección A.W.G. mm ²							
			D W	F	L	H	D Int	D Ext	
P.V.C	100	22-16 A.W.G. 0.5-1.5 mm ²	3,9	8,7	22,5	10,5	1,7	4,1	TE-CH15-40
	100	16-14 A.W.G. 1.5-2.5 mm ²	3,9	8,7	22,5	10,5	2,3	4,9	TE-CH25-40
	100	12-10 A.W.G. 4-6 mm ²	4,9	8,8	25,0	13,0	3,4	6,7	TE-CH60-50

ENCHUFABLES MACHO CILÍNDRICO DOBLE CASQUILLO



		Sección A.W.G. mm ²							
			D W	F	L	H	D Int	D Ext	
P.V.C	100	22-16 A.W.G. 0.5-1.5 mm ²	4,0	8,7	22,0	11,0	1,7	4,1	TE-CM15-40
	100	16-14 A.W.G. 1.5-2.5 mm ²	4,0	8,7	22,0	11,0	2,3	4,5	TE-CM25-40
	100	12-10 A.W.G. 4-6 mm ²	5,0	8,9	24,0	13,0	3,4	6,5	TE-CM60-50

CONECTORES RÁPIDOS



		Sección A.W.G. mm ²			
			W	L	
P.V.C	100	22-18 A.W.G. 0.5-1.5 mm ²	19,5	30,5	TE-RC-100
	100	16-14 A.W.G. 1.5-2.5 mm ²	19,5	30,5	TE-RC-250
	100	12-10 A.W.G. 4-6 mm ²	20,0	32,0	TE-RC-600