

## HSC8 6-4



mm	Kg	Rango		Tag
		mm <sup>2</sup>	AWG	
175	0,36	0,08-6	24-10	<b>HSC8 6-4</b>

## HSC8 16-4



mm	Kg	Rango		Tag
		mm <sup>2</sup>	AWG	
210	0,52	4-16	12-6	<b>HSC8 16-4</b>

## LY-05H

Conectores RG



8,1 mm	6,5 mm	5,4 mm	-	2,6 mm	1,72 mm	Tag
55, 58, 59, 62, 5, 6, 21, 140, 141, 142, 143, 210, 212, 222, 223, 303, 304, 400, BELDEN 8279, 8281, 9231, 9141						<b>LY-05H</b>

## BN-03C8

Terminal termoretráctil



mm	Kg	Rango		Tag
		mm <sup>2</sup>	AWG	
265	0,6	0,5-10	22-8	<b>BN-03C8</b>

## CRIMPER 25 N D4



mm	Sección (mm <sup>2</sup> )	Tag
230	10,0 - 25,0	<b>Crimper 25 D4</b>

## KH-230

Terminal de cobre y aluminio



Aplicación	Kg	Rango			Tag
		DIN (mm <sup>2</sup> )	AWG	mm	
Terminal	4,8	10-240		978	<b>KH-230</b>
Aluminio			8-400MCM		
Cobre			8-500MCM		

## KH-150

Terminal de cobre y aluminio

- Ajuste por tornillo: 10-120mm<sup>2</sup> • Aluminio: AWG8-4/0
- Cobre: AWG8-250MCM



mm	Kg	Rango			Tag
		DIN (mm <sup>2</sup> )	AWG	JIS (mm <sup>2</sup> )	
595	3,5	10-120	8-250	8-100	<b>KH-150</b>

## LY03C-5D

Kit herramientas



Descripción	Tag	Tag	
LY-03C Herramientas adicionales	Desnudos	DIES (LY-03C)	<b>LY03C-5D</b>
	Aislados	DIES (LY-03B)	
	Punteras	DIES (LY-04WF)	
	Punteras	DIES (LY-16WF)	
		DIES (LY-10)	