





REGLETAS CIEGAS TRANSPARENTES



TENSIÓN NOMINAL: 450 V






GRADO DE PROTECCIÓN: IP 20

CERTIFICACIONES:   

		SECCIÓN					
			ANCHO	ALTO	LARGO	Ø INT.	
25	450	2 x 1,5	16,5	15,5	90	3,2	B15
25	450	2 x 2,5	20	18,5	110	4	B25
25	450	2 x 4,0	22,2	19,7	116	4,5	B40
25	450	2 x 6,0	24,5	22	137	8	B60
10	300	2 x 10	29	25	157	7,5	B100
10	240	2 x 16	34,7	31	100	9,5	B160
25	200	2 x 25	38,5	40	22	12	B250
10	160	2 x 35	45,5	42,8	24,5	14	B350



BORNAS HILO PASANTE



			SECCIÓN				
				ANCHO	ALTO	LARGO	
PA	10	100	6,00	2,82	2,09	15,20	RGBR-06
	10	100	10,00	2,78	2,37	20,00	RGBR-10
	10	100	16,00	2,75	2,59	21,20	RGBR-16
	10	120	25,00	2,47	2,89	22,50	RGBR-25
	10	80	35,00	2,89	3,46	26,20	RGBR-35
	1	20	50,00	3,12	4,26	5,78	RGBR-50
	1	20	70,00	3,78	5,12	6,87	RGBR-70

BORNA SYGMA



	SECCIÓN	
1	16 mm	NSYS16
1	25/35 mm	NSYS25-35
1	50 mm	NSYS50
1	70 mm	NSYS70
1	95/100 mm	NSYS95-100