

## LK-325A

Cobre y aluminio

· Apertura: 32mm



mm	Kg	Rango		Tag
		mm <sup>2</sup>	AWG	
250	0,7	240	600MCM	<b>LK-325A</b>

## LK-520A

Cobre y aluminio

· Apertura: 52mm



mm	Kg	Rango		Tag
		mm <sup>2</sup>	AWG	
270	0,9	400	750MCM	<b>LK-520A</b>

## LY-700F

Pelador de cable



mm	Rango separación	Tag
	mm <sup>2</sup>	
170	0,2-6	<b>LY-700F</b>

## KN-228

Acero inoxidable



mm	Kg	Rango	Tag
		Fibra de vidrio & Aramid Fabrics	
125	0,1	<b>KN-228</b>	

## SW-867-A7

Juego destornilladores aislados

· 1000 voltios



Especificación	⊕ ⊖	Tag
0,5x3x80 mm	⊖	<b>SW-867-A7</b>
1x5,5x125 mm		
1,2x6,5x150 mm		
PH0x75 mm	⊕	
PH1x75 mm		
PH2x100 mm		
Volt Tester 145 mm (120-250V)		

## KH-503 9"



Size tipe	Aplicación			Tag
	Pela cables	Corte de tornillo	Crimping	
INCH	AWG			<b>KH-503A</b>
	10	4-40	Preaislado	
	12	6-32	AWG	
	14	8-32	22-18	
	16	10-24	16-14	
	18	10-32	12-10	
20-22				

## KH-502B 8"



Size tipe	Aplicación			Tag
	Pela cables	Corte de tornillo	Crimping	
MM	6		Preaislado 1,5/2,5/6 sqmm	<b>KH-502B</b>
	4	M2,5		
	2,5	M3		
	1,5	M3,5	Terminales desnudos 1,5/2,5/4,5	
	1	M4		
0,75	M5			