

TUBO POLIPROPILENO PP-BS



MATERIAL








- Polipropileno con protección contra incendios

TEMPERATURA DE TRABAJO

- -40°C/ 125°C

CARACTERÍSTICAS

- Temperatura máxima (240H) 150°C

|  |  |  |  Int. mm x  Ext. mm |  Cerrado |  Abierto |
|---|---|---|---|---|---|
| | 200 | 3 | 2,8 x 5,1 | 1930003 | 1930303 |
| | 100 | 4,5 | 5,0 x 7,1 | 1930004 | 1930304 |
| | 100 | 6 | 6,0 x 9,2 | 1930006 | 1930306 |
| | 50 | 7,5 | 6,9 x 9,9 | 1930007 | 1930307 |
| PG 7 | 50 | 8,5 | 8,5 x 11,6 | 1930008 | 1930308 |
| PG 9 | 50 | 10 | 10,1 x 12,7 | 1930010 | 1930310 |
| PG 11 | 50 | 12 | 12,0 x 15,6 | 1930012 | 1930312 |
| PG 11 | 50 | 13 | 12,9 x 15,8 | 1930013 | 1930313 |
| PG 13,5 | 50 | 14 | 14,5 x 18,3 | 1930014 | 1930314 |
| | 50 | 16 | 15,2 x 18,8 | 1930016 | 1930316 |
| PG 16 | 50 | 17 | 16,8 x 21,0 | 1930017 | 1930317 |
| | 50 | 19 | 19,4 x 24,0 | 1930019 | 1930319 |
| PG 21 | 50 | 22 | 21,8 x 25,5 | 1930022 | 1930322 |
| PG 21 | 50 | 23 | 23,7 x 28,0 | 1930023 | 1930323 |
| | 25 | 26 | 26,4 x 31,3 | 1930026 | 1930326 |
| PG 29 | 25 | 29 | 29,3 x 33,9 | 1930029 | 1930329 |
| PG 36 | 25 | 37 | 36,7 x 42,0 | 1930037 | 1930337 |
| PG 48 | 25 | 50 | 47,8 x 53,6 | 1930050 | 1930350 |