

## BORNES BIMETÁLICOS SIMPLES



Sección cable mm <sup>2</sup>			
MIN	MAX		
6	50	50	<b>3.030</b>
6	95	30	<b>3.031</b>
25	150	20	<b>3.032</b>
50	240	5	<b>3.033</b>

## BORNES BIMETÁLICOS DOBLES



Sección cable mm <sup>2</sup>			
MIN	MAX		
2x6	2x50	50	<b>3.034</b>
2x6	2x95	15	<b>3.035</b>
2x25	2x150	10	<b>3.036</b>
2x50	2x240	5	<b>3.037</b>

## BORNES BIMETÁLICOS DE PALA



Sección cable mm <sup>2</sup>			
MIN	MAX		
6	50	50	<b>3.038</b>
2x6	2x50	50	<b>3.039</b>

## BRIDAS DERIVACIÓN Y CONEXIÓN



Sección cable mm <sup>2</sup>			
MIN	MAX		
4	16	100	<b>3.040</b>
6	25	100	<b>3.042</b>
10	70	100	<b>3.041</b>

## BORNES DERIVACIÓN CON CAPUCHÓN



Sección cable mm <sup>2</sup>			
MIN	MAX		
95	-	50	<b>3.440</b>
95	95	30	<b>3.441</b>
95	-	30	<b>3.442</b>
95	95	20	<b>3.443</b>
150	-	20	<b>3.444</b>
150	150	10	<b>3.445</b>
150	-	10	<b>3.446</b>
150	150	10	<b>3.447</b>
240	-	5	<b>3.448</b>
240	240	5	<b>3.449</b>